
## **Product Features**

## **PMC-010**

## **DIGITAL PAGING CONSOLE**

- Worked with ZS-9810
  - Capacity of managing 30 paging selector
- Maximum remote control distance of up to 1km
  - Microphone volume control
- RCA line input and output
- Built-in chime and chime volume control
- Cascade-able up to 16 units thru RJ45 ports





## **Technical Specifications**

Input	MIC: $600\Omega$ , $10\text{mV}$ , Unbalanced LINE: $10\text{k}\Omega$ , $775\text{mV}$ , Unbalanced
Output	Balanced
Frequency Response	MIC: 100Hz – 15kHz; Line: 30Hz – 18kHz
S/N Ratio	MIC Input: 60dB; LINE Input: 80dB
Controls	Chime MIC Vol controls, 160 channel selectors, chime button, power switch
Indicators	Power LED, 10 paging channel LEDs
Protection	AC fuse, 0.5A
Power Supply	DC 24V
Power Consumption	10W
Communication Protocol	RS422
Communication Input	RJ45
Communication Speed	4800bps
Weight	1.25kg
Dimension (W x D x H)	220mm x 150mm x 50mm
Material & Finish	Panel: Steel Plate; black Case: Steel Plate; black Side Board: Plastic; black